

Edixeon S White Series Datasheet



Features :

- Various colors
- More energy efficient than incandescent and most halogen lamps
- Low voltage operation
- Instant light
- Long operating life

Table of Contents

General Information.....	3
Absolute Maximum Ratings.....	4
Characteristics.....	4
Luminous Flux Characteristic.....	5
Mechanical Dimensions.....	6
Characteristic curve.....	7
Reflow Profile.....	14
Reliability.....	15
Product Packaging Information.....	16
Revision History.....	17
About Edison Opto.....	17

General Information

Introduction

Edixeon S series emitters are one of the highest flux LEDs in the world by Edison Opto. Edixeon S series emitters are designed to satisfy more and more Solid-State lighting High Power LED applications for brilliant world such as flash light, indoor and outdoor decoration light. Unlike most fluorescent sources, Edixeon contains no mercury and has more energy efficient than other incandescent light source.

Ordering Code Format

<u>2</u> X1	<u>E</u> X2	<u>S 1</u> X3	<u>0 x</u> X4	<u>x W</u> X5	<u>x x</u> X6	<u>0 0 0</u> X7	<u>x x x</u> X8		
X1		X2		X3		X4		X5	
Type	Component		Series		Wattage		Color		
2	Emitter	E	Edixeon	S1	S1 Series	01	1W	CW	Cool White
						03	3W	NW	Neutral White
								WW	Warm White
X6		X7		X8					
Internal code		PCB Board		Serial Number					
-	-	000	-	-	-				

Absolute Maximum Ratings

Parameter	Symbol	Value	Units
DC Forward Current ^[1]	(1W) (3W) I_F	350 700	mA
Peak Pulsed Current; (tp≤100μs, Duty cycle=0.25) ^[2]	(1W) (3W) I_{pulse}	500 1000	mA
Reverse Voltage	V_R	5	V
Drive Voltage	V_D	5	V
LED Junction Temperature ^[3]	T_J	125	°C
Operating Temperature	-	-30 ~ +110	°C
Storage Temperature	-	-40 ~ +120	°C
ESD Sensitivity (HBM)	-	2,000	V
Soldering Temperature	-	260	°C
Manual Soldering Time at 260°C(Max.)	-	5	Sec.

Notes:

1. Proper current derating must be observed to maintain junction temperature below the maximum at all time.
2. LEDs are not designed to be driven in reverse bias.
3. tp: Pulse width time
4. Allowable reflow cycles are 3 times for each LED.

Characteristics

Parameter	Symbol	Value	Units
Viewing Angle	$2\Theta_{1/2}$	135	Degree
Forward voltage (Typ.)	V_F	3.4	V
Thermal resistance	-	11	°C/W
$\Delta V_F / \Delta T$	$\Delta V_F / \Delta T$	-2	mV/°C
CCT	λ_d	CW: 5,000-10,000 NW: 3,800-5,000 WW: 2,670-3,800	K
CRI	-	CW: 70&80 NW: 80 WW: 80	-
JEDEC Moisture Sensitivity	-	Level 2a Floor Life Conditions: ≤30°C / 60% RH Soak Requirements(Standard) Time (hours): 120+1/-0 Conditions: 60°C / 60% RH	-

Notes:

1. Wavelength is measured with an accuracy of ± 0.5nm.
2. CCT is measured with an accuracy of ± 5%.
3. Viewing angle is measured with an accuracy of ± 5%.
4. Color Rendering index CRI tolerance: ± 2.

Luminous Flux Characteristic

Luminous Flux Characteristics, $T_j=25^{\circ}\text{C}$.





Color	Wattage (W)	Group	Min. Luminous Flux(lm)	Max. Luminous Flux(lm)	Forward Current (mA)	Order Code
Cool White	1	U3	100	110	350	2ES101CW06000001 2ES101CW14000001
		V1	110	120		
		V2	120	130		
		V3	130	140		
		V4	140	150		
	3	W1	160	180	700	2ES103CW06000001 2ES103CW14000001
		W2	180	200		
		W3	200	220		
Neutral White	1	U2	90	100	350	2ES101NW32000001
		U3	100	110		
		V1	110	120		
		V2	120	130		
	3	W1	160	180	700	2ES103NW32000001
		W2	180	200		
		W3	200	220		
Warm White	1	T3	80	86.5	350	2ES101WW32000001
		U1	86.5	90		
		U2	90	100		
		U3	100	110		
	3	V5	150	160	700	2ES103WW32000001
		W1	160	180		
		W2	180	200		


Notes:

1. Flux is measured with an accuracy of $\pm 10\%$.
2. All Cool White, Neutral White, Warm White emitters are built with InGaN.

Mechanical Dimensions

Emitter Type Dimension



Emitter Color	Slug at the bottom of the electrode	Circuit
CW/NW/WW	No electrode	


Edixeon S series dimensions and circuits

Notes:

1. All dimensions are in mm.
2. It is strongly recommended that the temperature of lead doesn't exceed 55°C.
3. It is important that the slug can't contact aluminum surface, It is strongly recommended that there should coat a uniform electrically isolated heat dissipation film on the aluminum surface.


Characteristic curve

Color Spectrum




Color Spectrum at a typical CCT for Edixeon S White

Radiation Angle




Radiation Angle for Edixeon S White

Forward Current vs. Forward Voltage




Forward Current vs. Forward Voltage for 1W White




Forward Current vs. Forward Voltage for 3W White

Relative Luminous Intensity vs. Forward Current




Relative Luminous Intensity vs. Forward Current for 1W White




Relative Luminous Intensity vs. Forward Current for 3W White

Relative Luminous Flux vs. Junction Temperature




Relative Luminous flux vs. junction temperature for Edixeon S White

Forward Voltage vs. Junction Temperature




Forward voltage vs. junction temperature for Edixeon S White

$\Delta x, \Delta y$ vs. Forward Current




$\Delta x, \Delta y$ vs. Forward Current for 1W White




$\Delta x, \Delta y$ vs. Forward Current for 3W White

$\Delta x, \Delta y$ vs. Junction Temperature




$\Delta x, \Delta y$ vs. Junction temperature for Edixeon S White

Maximum Current vs. Ambient Temperature




Maximum Current vs. Ambient Temperature for 1W White



Maximum Current vs. Ambient Temperature for 3W White

Reflow Profile

The following reflow profile is from IPC/JEDEC J-STD-020D which provided here for reference.



Reflow Profiles

Classification Reflow Profiles

Profile Feature	Pb-Free Assembly
Preheat & Soak	
Temperature min (T_{min})	150°C
Temperature max (T_{max})	200°C
Time (T_{min} to T_{max}) (t_s)	60-120 seconds
Average ramp-up rate (T_{max} to T_p)	$3^\circ\text{C/second max.}$
Liquidous temperature (T_L)	217°C
Time at liquidous (t_L)	60-150 seconds
Peak package body temperature (T_p)*	$255^\circ\text{C} \sim 260^\circ\text{C}^*$
Classification temperature (T_c)	260°C
Time (t_p)** within 5°C of the specified classification temperature (T_c)	30** seconds
Average ramp-down rate (T_p to T_{max})	$6^\circ\text{C/second max.}$
Time 25°C to peak temperature	8 minutes max.

Notes:

- * Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.
- ** Tolerance for time at peak temperature (t_p) is defined as a supplier minimum and a user maximum.

Reliability


NO .	Test Item	Test Condition	Remark
1	Temperature Cycle	-40°C~100°C 30, 30, mins	100 Cycle
2	Thermal Shock	-40°C~100°C 15, 15 mins \leq 10 sec	100 Cycle
3	Resistance to Soldering Heat	T _{SOL} =260°C, 30 sec	3 times
4	Moisture Resistance	25°C~65°C 90% RH 24 hrs / 1 cycle	10 Cycle
5	High-Temperature Storage	T _A =100°C	1,000 hrs
6	Humidity Heat Storage	T _A =85°C RH=85%	1,000 hrs
7	Low-Temperature Storage	T _A =-40°C	1,000 hrs
8	Operation Life test	25°C	1,000 hrs
9	High Temperature Operation Life test	85°C	1,000 hrs
10	High Humidity Heat Life Test	85°C, 85%RH	1,000 hrs
11	ON/OFF Test	30 sec ON, 30 sec OFF	10W times

Failure Criteria


Item	Criteria for Judgment	
	Min.	Max.
Lumen Maintenance	85%	-
$\Delta u'v'$	-	0.006
Forward Voltage	-	Initial Data x 1.1
Reverse Current	-	10 μ A
Resistance to Soldering Heat	No dead lamps or visual damage	

Product Packaging Information


Tape and Reel Dimension





Edixeon Emitter



1000pcs LEDs inside



2 bags in 1 box



5 boxes in 1 carton

Note : 445*410*415 (Tolerance : $\pm 5\text{mm}$)

Revision History

Versions	Description	Release Date
1	Establish order code information	2014/05/19

About Edison Opto

Edison Opto is a leading manufacturer of high power LED and a solution provider experienced in LDMS. LDMS is an integrated program derived from the four essential technologies in LED lighting applications- Thermal Management, Electrical Scheme, Mechanical Refinement, Optical Optimization, to provide customer with various LED components and modules. More Information about the company and our products can be found at www.edison-opto.com

Copyright©2014 Edison Opto. All rights reserved. No part of publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photo copy, recording or any other information storage and retrieval system, without prior permission in writing from the publisher. The information in this publication are subject to change without notice.

www.edison-opto.com

For general assistance please contact:
service@edison-opto.com.tw

For technical assistance please contact:
LED.Detective@edison-opto.com.tw